

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Claims 1-50 (Cancelled)

51. (Previously Presented) A method comprising:

adding a first gas to an enclosure having a second gas through an inlet port having a shape to distribute a flow of the first gas over a length of a side of the enclosure, the first gas having a different composition than the second gas, the enclosure being between a mask protective device, a patterned mask, and walls connecting the mask protective device with the patterned mask; and

removing at least a portion of the second gas from the enclosure through one or more outlet ports.

52. (Previously Presented) The method of claim 51, wherein the inlet port comprises a slit in a wall.

53. (Previously Presented) The method of claim 51, wherein said adding comprises adding the first gas through a plurality of inlet ports.

54. (Previously Presented) The method of claim 51, wherein said removing comprises removing the second gas by vacuum.

55. (Previously Presented) The method of claim 51, wherein said adding comprises adding the first gas through an inlet port that is smaller than an outlet port.

Claims 56-63 (Cancelled)

64. (New) The method of claim 51, wherein said adding comprises adding the first gas through a plurality of openings of the inlet port, which are on the side.
65. (New) The method of claim 51, wherein said adding comprises adding the first gas through at least five openings of the inlet port.
66. (New) The method of claim 51, wherein said adding comprises adding the first gas through a plurality of openings of the inlet port that are arranged to encourage plug flow through the enclosure.
67. (New) The method of claim 51, wherein said adding and said removing comprise adding the first gas by diffusion and removing the second gas by diffusion.
68. (New) The method of claim 67, further comprising heating a gas in the enclosure to increase a diffusion coefficient.
69. (New) A method comprising:
- adding a first gas to an enclosure including a second gas through a vent to distribute a flow of the first gas over a length of a side of the enclosure, the first gas having less total oxygen and carbon than the second gas, the enclosure being between a pellicle, a mask, and walls connecting the pellicle with the mask; and removing at least a portion of the second gas from the enclosure.
70. (New) The method of claim 69, wherein said adding comprises adding the first gas through a slit in a wall.
71. (New) The method of claim 69, wherein said adding comprises adding the first gas through a plurality of openings in a wall.

- 72. (New) The method of claim 71, wherein two or more of the plurality of openings are on a same side of the enclosure.
- 73. (New) The method of claim 69, wherein said adding comprises adding the first gas through an inlet opening that is smaller than an outlet opening used to remove the second gas.
- 74. (New) The method of claim 69, wherein said adding comprises adding the first gas through at least five openings of the vent.
- 75. (New) The method of claim 74, wherein the at least five openings are on a same side of the enclosure.
- 76. (New) The method of claim 69, wherein said adding comprises adding the first gas through a plurality of openings that are arranged to encourage plug flow through the enclosure.
- 77. (New) The method of claim 69, wherein said removing comprises removing the second gas by creating a vacuum in the enclosure.